


## Z9A-YRB REDUCING COMBINATION WYE and 45° ELBOW

### Engineering Specification:

ASTM-F1412, F.R.P.P. - 210

ZURN Z9A-YRB REDUCING COMBINATION WYE and 45° ELBOW – Flame-retardant polypropylene reducing combination wye and 1/8 bend fitting assembly.



### Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal


Model No.	Dimensions in Inches [mm]						
	Nom. Pipe Size	Reducer Size	A	B	C	F	L
Z9A-YRB-2 x 112	2 [51]	2 x 1-1/2 [51 x 38]	5-15/16 [135]	4-1/2 [114]	13/16 [21]	8-15/16 [227]	7-25/32 [198]
Z9A-YRB-3 x 112	3 [76]	3 x 1-1/2 [76 x 38]	7-23/32 [196]	7-1/4 [184]	1-5/8 [41]	8-11/16 [221]	12-27/32 [326]
Z9A-YRB-3 x 2	3 [76]	3 x 2 [76 x 51]	8-3/32 [206]	7-1/4 [184]	1-5/8 [41]	8-15/16 [227]	12-27/32 [326]
Z9A-YRB-4 x 112	4 [102]	4 x 1-1/2 [102 x 38]	9-1/16 [230]	9-1/16 [230]	1-7/8 [48]	10-9/32 [261]	14-15/16 [379]
Z9A-YRB-4 x 2	4 [102]	4 x 2 [102 x 51]	9-11/32 [237]	9-1/16 [230]	1-7/8 [48]	10-1/2 [267]	14-15/16 [379]
Z9A-YRB-4 x 3	4 [102]	4 x 3 [102 x 76]	10-15/16 [278]	9-1/16 [230]	1-7/8 [48]	11-1/16 [281]	14-15/16 [379]
Z9A-YRB-6 x 2	6 [152]	6 x 2 [152 x 51]	16-3/8 [416]	11-1/8 [283]	1-3/4 [44]	15-7/8 [403]	17-3/16 [437]
Z9A-YRB-6 x 3	6 [152]	6 x 3 [152 x 76]	17-1/32 [433]	11-1/8 [283]	1-3/4 [44]	16-17/32 [419]	17-3/16 [437]
Z9A-YRB-6 x 4	6 [152]	6 x 4 [152 x 102]	14-7/8 [378]	11-1/8 [283]	1-3/4 [44]	14-3/8 [365]	17-3/16 [437]

## Z9A-YY 45° DOUBLE WYE

### Engineering Specification:

ASTM-F1412, F.R.P.P. - 210

ZURN Z9A-YY 45° DOUBLE WYE – Flame-retardant polypropylene double wye fitting assembly.



### Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal

Model No.	Dimensions in Inches [mm]					
	Nom. Pipe Size	A	B	C	E	L
Z9A-YY-112	1-1/2 [38]	3-1/8 [79]	3-3/16 [81]	21/32 [17]	4-3/13 [106]	6-9/16 [167]
Z9A-YY-2	2 [51]	4-1/16 [103]	4-1/2 [114]	13/16 [21]	5-11/32 [136]	7-7/8 [200]
Z9A-YY-3	3 [76]	6 [152]	7-1/4 [184]	1-5/8 [41]	7-3/4 [197]	12-9/16 [319]
Z9A-YY-4	4 [102]	7 [178]	9-1/16 [230]	1-5/8 [41]	8-3/4 [222]	14-11/16 [373]
Z9A-YY-6	6 [152]	11-1/8 [283]	11-1/8 [283]	1-3/4 [44]	13-1/4 [337]	17-3/16 [437]