

MODEL ZW204 - Non-Modulating Float Valve Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity: _____

Size: (Check one) DN32 DN40 DN50 DN65 DN80 DN100
 DN150 DN200 DN250 DN300 DN350 DN400

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Function Options:

- Check one "C" Option * - Check Valve with Isolation Valve
 "L" Option * - Closing Speed Control (Standard on DN200 and larger)
 "O" Option * - Opening Speed Control

Valve body is ductile iron, epoxy coated

Body Options:

- Check all that apply Standard - Full Port Globe Body
 "A" Option - Angle Style Body (DN32 - DN250)
 "R" Option - Reduced Port Body (DN80 - DN250 Flanged only)



DIRECTION OF FLOW ⇒
("VM" OPTION)

End Connections (Check one)

Size Range (DN40 - DN400)

- | Options | Description | Options | Description |
|-----------------------------------|-------------------------------------------------------|----------------------------------|--------------------------------------------------|
| <input type="checkbox"/> Standard | - ANSI Class 150 Flanges | <input type="checkbox"/> "PN6" | - ISO Class PN6 Flanges |
| <input type="checkbox"/> "BSD" | - BS10/AS2129 Table D Flanges | <input type="checkbox"/> "PN10" | - ISO Class PN10 Flanges |
| <input type="checkbox"/> "BSE" | - BS10/AS2129 Table E Flanges | <input type="checkbox"/> "PN16" | - ISO Class PN16 Flanges |
| <input type="checkbox"/> "BSF"* | - BS10/AS2129 Table F Flanges | <input type="checkbox"/> "PN25"* | - ISO Class PN25 Flanges |
| <input type="checkbox"/> "BSH"* | - BS10/AS2129 Table H Flanges | | |
| <input type="checkbox"/> "G" | - IPS Grooved, ANSI/AWWA C 606 | Size Range (DN32 - DN80) | |
| <input type="checkbox"/> "BG" | - Grooved DN65, or DN150 (76.1 mm or 165.1mm pipe OD) | <input type="checkbox"/> "TH" | - NPT Threaded, ANSI/ASME B1.20.1 |
| <input type="checkbox"/> "Y"* | - ANSI Class 300 Flanges | <input type="checkbox"/> "BS" | - Threaded British Pipe Parallel BSPP/G size ISO |
| | | <input type="checkbox"/> "BT" | - Threaded British Pipe Tapered BSPT/Rc size ISO |

Main Valve Option:

- Check all that apply Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
 "V" Option * - Viton Rubber Internals, Rated 82°C (DN32 - DN150)
 "Z" Option *1 - Visual Position Indicator
 "SO" Option *1 - Limit Switch Open Trip
 "SC" Option *1 - Limit Switch Closed Trip
 "SD" Option *1 - Limit Switch Dual Trip

Pilot Options:

- Standard - Isolation Valves, and "Wye" Strainer
 Standard - Copper Tubing and Brass Fittings
 "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings & Copper Tubing. "GL" Option included)
 "SH" Option * - Stainless Steel Braided Hoses (only replaces Copper Tubing, with "VM" Option Only)



DIRECTION OF FLOW ⇒
STANDARD - REMOTELY MOUNTED FLOAT

- Must check one** Standard - Remotely Mounted Float
 "VM" Option * - Valve Mounted Float Pilot **SEE IMAGES**
- Check one Standard - 60cm Standard Float Rod (Stainless Steel Rod & Float)
 "R1" Option * - 30cm Float Rod Extension (90cm total length)
 "R2" Option * - 60cm Float Rod Extension (120cm total length)
 "R3" Option * - 90cm Float Rod Extension (150cm total length)

Optional "RV" Option - Pilot on Reverse Side

*Adder to standard price applies

¹Limit switch and position indicator options cannot be combined

1747 Commerce Way
 Paso Robles, CA 93446
 Phone: 855-663-9876
 Fax: 805-237-7197

Customer Service Representatives available
 Monday through Friday 5:30 a.m. to 5:00 p.m., PST
 Fax completed forms to 805-237-7197, attention: Sales
 Call 855-663-9876, wilkinscs@zurn.com
 or visit us online at www.zurn.com

