

# MODEL ZW204 - Non-Modulating Float Valve Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

## Required Valve Information

Quantity: \_\_\_\_\_

Size:  1-1/4" (DN32)     1-1/2" (DN40)     2" (DN50)     2-1/2" (DN65)     3" (DN80)     4" (DN100)  
 6" (DN50)     8" (DN200)     10" (DN250)     12" (DN300)     14" (DN350)     16" (DN400)

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

**Caution:** The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

## Function Options:

- Check all that apply
- "C" Option \* - Check Valve with Isolation Valve
  - "L" Option \* - Closing Speed Control (Standard on 8" (DN200) and larger)
  - "O" Option \* - Opening Speed Control

Valve body is ductile iron, epoxy coated

## Body Options:

- Check one
- Standard - Full Port Globe Body
  - "A" Option - Angle Style Body (1-1/4" (DN32) - 10" (DN250))
  - "R" Option - Reduced Port Body (3" (DN80) - 10" (DN250) Flanged only)



DIRECTION OF FLOW →  
("VM" OPTION)

## End Connections (Check one)

## Size Range (1-1/2" - 16", DN40 - DN400)

- | Options                           | Description  | Options                                      | Description                                      |
|-----------------------------------|--|--|--|
| <input type="checkbox"/> Standard | - ANSI Class 150 Flanges                             | <input type="checkbox"/> "PN6"               | - ISO Class PN6 Flanges                          |
| <input type="checkbox"/> "BSD"    | - BS10/AS2129 Table D Flanges                        | <input type="checkbox"/> PN10"               | - ISO Class PN10 Flanges                         |
| <input type="checkbox"/> "BSE"    | - BS10/AS2129 Table E Flanges                        | <input type="checkbox"/> "PN16"              | - ISO Class PN16 Flanges                         |
| <input type="checkbox"/> "BSF"*   | - BS10/AS2129 Table F Flanges                        | <input type="checkbox"/> "PN25"*             | - ISO Class PN25 Flanges                         |
| <input type="checkbox"/> "BSH"*   | - BS10/AS2129 Table H Flanges                        | <b>Size Range (1-1/4" - 3", DN32 - DN80)</b> |  |
| <input type="checkbox"/> "G"      | - IPS Grooved, ANSI/AWWA C 606                       | <input type="checkbox"/> "TH"                | - NPT Threaded, ANSI/ASME B1.20.1                |
| <input type="checkbox"/> "BG"     | - Grooved 2-1/2", or 6" (76.1 mm or 165.1mm pipe OD) | <input type="checkbox"/> "BS"                | - Threaded British Pipe Parallel BSPP/G size ISO |
| <input type="checkbox"/> "Y"*     | - ANSI Class 300 Flanges                             | <input type="checkbox"/> "BT"                | - Threaded British Pipe Tapered BSPT/Rc size ISO |

## Main Valve Option:

- Check all that apply
- Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
  - "V" Option \* - Viton Rubber Internals, Rated 180°F (1-1/4" - 6")
  - "Z" Option \*1 - Visual Position Indicator
  - "SO" Option \*1 - Limit Switch Open Trip
  - "SC" Option \*1 - Limit Switch Closed Trip
  - "SD" Option \*1 - Limit Switch D Trip



DIRECTION OF FLOW →  
STANDARD - REMOTELY MOUNTED FLOAT

## Pilot Options:

- Check all that apply
- Standard - Isolation Valves, and "Wye" Strainer
  - Standard - Copper Tubing and Brass Fittings
  - "SP" Option \* - All Stainless Steel Pilotry (replaces all Brass Fittings & Copper Tubing. "GL" Option included)
  - "SH" Option \* - Stainless Steel Braided Hoses (only replaces Copper Tubing, with "VM" Option only)
- Must check one**
- Standard - Remotely Mounted Float
  - "VM" Option \* - Valve Mounted Float Pilot SEE IMAGES
- Check one
- Standard - 2' Standard Float Rod (Stainless Steel Rod & Float)
  - "R1" Option \* - 1' Float Rod Extension (3' total length)
  - "R2" Option \* - 2' Float Rod Extension (4' total length)
  - "R3" Option \* - 2' Float Rod Extension (4' total length)

Optional  "RV" Option - Pilot on Reverse Side

\*Adder to standard price applies

<sup>1</sup>Limit switch and position indicator options cannot be combined

1747 Commerce Way  
Paso Robles, CA 93446  
Phone: 855-663-9876  
Fax: 805-237-7197

Customer Service Representatives available  
Monday through Friday 5:30 a.m. to 5:00 p.m., PST  
Fax completed forms to 805-237-7197, attention: Sales  
Call 855-663-9876, wilkinscs@zurn.com  
or visit us online at www.zurn.com

