



ZER6000PL-CPM

Sensor Operated Battery Powered Flush Valve
For Water Closets

TAG _____

Architectural/Engineering Specification:

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with chloramine resistant, dual seal diaphragm with a clog resistant by-pass. The valve incorporates a 6VDC motor actuator, a battery powered automatic sensor, high impact resistant polycarbonate housing and chrome plated metal cover with manual override push button and 10 degree angled sensor.

Product Features:

- Control stop with internal siphon-guard protection, vandal resistant stop cap, sweat solder kit, and cast wall flange with set screw
- High back pressure Vacuum Breaker with one piece hex
- Chloramine-resistant internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

Compliance and Certification:

- Complies with ASSE 1037/ASME A112.1037/CSA B125.37
- ADA Compliant



*This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



Flow Options:

	Flush Volume	WaterSense* Labeled
-ONE	1.1 gpf	✓
-HET	1.28 gpf	✓
-WS1	1.6 gpf	
-Standard	3.5 gpf	

Suffix Options:

- TFB Floor Mount 12" Rough In
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support
- Other

Architectural/Engineering Approval



ZER6000PL-CPM

Sensor Operated Battery Powered Flush Valve
For Water Closets

TAG _____

Rough-in/Overview dimensions

