



ZER6003PL-CPM

Sensor Operated Battery Powered Flush Valve For 3/4" TAG Urinals

Architectural/Engineering Specification:

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with chloramine resistant, dual seal Zurn's AquaFlush® TPE diaphragm with a clog resistant by-pass. The valve incorporates a 6VDC motor actuator, a battery powered automatic sensor and chrome plated metal cover with manual override push button.

Product Features:

- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection and vandal resistant stop cap, Sweat solder kit, wall flange with set screw.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

Compliance and Certification:

- ADA Compliant



*This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.



Flow Options:

	Flush Volume	WaterSense* Labeled
-ULF	0.125 gpf	✓
-EWS	0.5 gpf	✓
-WS1	1.0 gpf	

Suffix Options:

- TFB Triple Filtered By-pass
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support
- Other

Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



ZER6003PL-CPM

Sensor Operated Battery Powered Flush Valve For 3/4" TAG
Urinals

Rough-in/Overview dimensions

