

**ARCHITECTURAL & ENGINEERING SPECIFICATION**

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve is ADA compliant with a non-hold open and no leak handle feature. Internal seals are made of chloramine resistant materials.

**PRODUCT FEATURES**

- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection and vandal resistant stop cap, Sweat solder kit, wall flange with set screw.
- High back pressure vacuum breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

**VALVE HEIGHT OPTIONS**

	DIMENSION A INCH [MM]
<b>-STANDARD</b>	11 1/2" [292]
<b>-1</b>	16" [406]
<b>-2</b>	24" [610]
<b>-3</b>	27" [686]

**COMPLIANCE AND CERTIFICATION:**

- ADA Compliant



\*This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



**FLOW OPTIONS**

	FLUSH VOLUME GPF	WATERSENSE* COMPLIANT
<b>-ULF**</b>	0.125	☑
<b>-EWS**</b>	0.5	☑
<b>-WS1</b>	1.0	

\*\* Not available with triple filter by-pass

**SUFFIX OPTIONS**

- BG BioCare ADAHandle
- D1 1" Supply
- L 1" [25mm] Metal Push Button
- L3 3" [76mm] Metal Push Button
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in/Overview dimensions

