



ARCHITECTURAL & ENGINEERING SPECIFICATION

Concealed, quiet diaphragm-type, rough brass flushometer valve. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve incorporates a 6VDC motor actuator, an automatic sensor with capacitive sensing override push button, high impact resistant polycarbonate housing and chrome plated plastic cover with manual override push button and 10 degree angled sensor.

PRODUCT FEATURES


- Zurn's AquaVantage® TPE diaphragm
 - Clog Resistant by-pass
 - Chloramine resistant
 - Dual seal
- Proprietary DR resistant low lead brass alloy
- Actuator
 - ZEMS 6 VDC Motorized Actuator
- Automatic Sensor
 - Fully configurable sensor range adjustment
 - 48 or 168 hour trap seal flush
 - Capacitive sensing push button override
- Electronic Override Button
- Control Stop
 - Internal siphon-guard protection
 - Sweat solder kit
- Vacuum Breaker
 - High back pressure
 - One piece hex coupling nut
- Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

COMPLIANCE AND CERTIFICATION

- ADA Compliant
- Watersense Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



FLOW OPTIONS

	FLUSH VOLUME GPF	WATERSENSE* COMPLIANT
-ULF*	0.125	☑
-EWS*	0.5	☑
-WS1	1.0	
-STANDARD	1.5	

* Not available with triple filter by-pass

ACCESSORIES (ORDER SEPARATE AS SPECIFIED)

- P6900-ACA 7.5VDC Plug-In ACA Power Supply
Powers up to 4 valves
- P6000-HW6 7.6VDC Hardwired Power Converter
Powers up to 8 valves
- P6000-MJ Mini Junction Box

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

ROUGH-IN/OVERVIEW DIMENSIONS

