



# Z6000AV-BWN

Exposed Flush Valve with Bedpan Washer for Water Closets

TAG \_\_\_\_\_

### Architectural/Engineering Specification:

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve is ADA compliant with a non-hold open and no leak handle feature. Internal seals are made of chloramine resistant materials.

### Product Features:

- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection and vandal resistant stop cap, Sweat solder kit, wall flange with set screw.
- Bedpan washer assembly with wall bracket and support rod.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

### Valve Height Options:

	Product No.	A
	Z6000AV-BWN	26 1/2" [673]
	Z6000AV-BWN1	34 3/8" [873]
	Z6000AV-BWN2	37 1/2" [953]

### Compliance and Certification:

- ADA Compliant



\*This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



### Flow Options:

	Flush Volume	Dual Flush	WaterSense* Labeled
<b>-ONE</b>	1.1 gpf		✓
<b>-HET</b>	1.28 gpf		✓
<b>-WS1</b>	1.6 gpf	1.6/1.1 gpf	
<b>-Standard</b>	3.5 gpf	3.5/2.4 gpf	

### Suffix Options:

- BG BioCare Handle
- H Handle on Front of Flush Valve
- L 1" [25] Metal Push Button
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

\*\* Not available with triple filter by-pass

Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



# Z6000AV-BWN

Exposed Flush Valve with Bedpan Washer for Water Closets

TAG \_\_\_\_\_

## Rough-in/Overview dimensions

