



ARCHITECTURAL & ENGINEERING SPECIFICATION

Concealed, quiet diaphragm-type, rough brass flushometer valve. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve is ADA compliant with a non-hold open and no leak push button feature. Internal seals are made of chloramine resistant materials.

PRODUCT FEATURES

- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection and vandal resistant stop cap, Sweat solder kit, wall flange with set screw.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

COMPLIANCE AND CERTIFICATION

- ADA Compliant
- WaterSense Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.

FLOW OPTIONS

	FLUSH VOLUME GPF	WATERSENSE* COMPLIANT
-ULF	0.125	☑
-EWS	0.5	☑
-WS1	1.0	
-STANDARD	1.5	

SUFFIX OPTIONS

- AP Access Panel
- BG BioCare Handle
- J Metal Oscilating ADA Handle
- L3 3" [76] Metal Push Button

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in dimensions/Overview dimensions

