



ARCHITECTURAL & ENGINEERING SPECIFICATION

Exposed, quiet diaphragm-type, chrome-plated flushometer valve with a polished exterior. Complete with Zurn's AquaFlush® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, linear filtered by-pass. The valve incorporates a motor actuator, an automatic sensor with capacitive sensing push button override, high impact resistant polycarbonate housing and chrome-plated plastic cover with manual override push button and 10 degree angled sensor.

PRODUCT FEATURES

- Proprietary dezincification resistant low lead brass alloy
- Control stop has internal siphon-guard protection, vandal resistant stop cap, sweat solder kit and wall flange with set screw
- High back pressure vacuum breaker with one piece hex coupling nut
- Chloramine resistant internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

COMPLIANCE AND CERTIFICATION:

- Complies with ASSE 1037 / ASME A112.1037 / CSA B125.37
- ADA Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.

POWER SUPPLY CHOICES (SOLD SEPARATELY)

- P6900-ACA-BA 7.6VDC Plug-In ACA Power Supply Powers up to 4 valves
- HW6 7.6VDC Hardwired Power Converter
- MJ Mini Junction Box

NOTE: For Hardwire applications furnish P6000-HW6 power converter. Order P6000-HW6 power converter separately.

The P6000-HW6 and P6000-MJ will power up to 8 sensor faucets.



FLOW OPTIONS

	FLUSH VOLUME GPF	WATERSENSE COMPLIANT
-ULF*	0.125	☑
-EWS*	0.5	☑
-WS1	1.0	
-STANDARD	1.5	

* Not available with triple filter by-pass

SUFFIX OPTIONS

- VP Vandal Resistant Stop Screw
- TFB Triple Filter By-pass
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support
- Other

VALVE HEIGHT OPTIONS

	DIMENSION A INCH [MM]
-STANDARD	11 1/2" [292]
-1	16" [406]
-2	24" [610]

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in/Overview dimensions:

