

## CONCEALED ARM CARRIER SYSTEM FOR WALL HUNG TAG LAVATORY W/ ADJUSTABLE UPRIGHTS & HEADER PLATES

Dimensional Data (inches and [ mm ]) are Subject to Manufacturing Tolerances and Change Without Notice SCALE 16 17 18 19 <u>20 21 2</u> 11 [279] MIN. 26 [660] MAX. OVERALL CARRIER WIDTH: MAXIMUM =  $34\frac{1}{8}$  [867] MINIMUM = 26 [660] [12] MIN. [381] MIN. 3 [85]  $1\frac{1}{16}$  [27] MAX. 22 [560] MAX. -LEVELING SCREW E#=1=F# EACH HEADER PLATE IS HORIZONTALLY ADJUSTABLE 2 [51] IN EITHER LEFT OR RIGHT DIRECTION. OCKING DEVICE 2 [51] [54] MIN. 2 [50] [64] MAX. -ADJUSTMENT SCREWS MUST BE LOCATED AT BOTTOM AS SHOWN. B# Н# 5음 [141] 1 [41] C# FINISHED TO RIM ANCHOR HOLES FOR EITHER 3 [10] (OPTIONAL) OR [ [13] ANCHORS (FURNISHED BY OTHERS).  $\frac{1}{2}$  [64] <u>↓</u> 6 [168] Approx. NOTES: Product #REFER TO ROUGH-IN GUIDE OF SPECIFIC FIXTURE FOR DIMENSION Wt. Lbs. No. \*\* WITH STANDARD SLEEVE LENGTH OF 4 [102] [kg] Z1231-EZR 45 [20] Two diagonally spaced anchors per foot are required for correct

## **ENGINEERING SPECIFICATION:** ZURN Z1231-EZR

Wall Hung Lavatory Support System complete with Dura-Coated upright supports made from structural carbon-steel square tubing, conforming to ASTM A500 Grade C standards, with welded steel plate mounting feet featuring separate bolt patterns for using either 3/8" [10mm] or 1/2" [13mm] anchors, both meeting OSHPD spacing requirements. Includes lower and upper EZ-installation plates, marked with an indexed ruler guide for accurate adjustability of upright spacing, from 15" [381mm] to 22" [560mm]. Individual slotted header plates with integral welded arm sleeves provide 2" [51mm] of additional horizontal adjustment per plate allowing for a total horizontal adjustment range of 11" [279mm] to 26" [660mm]. Arms are Dura-Coated cast iron and include leveling screws and soft-set elastomeric locking devices. Uprights, EZ-installation plates, and header plates are all factory assembled for easy installation. Carrier system exceeds load and deflection requirements when tested in accordance to ASME Standard A112.6.1M at any adjustment position.

**OPTIONS** (Check/specify appropriate options)

## **PREFIXES**

Z Dura-Coated System with Support Plate\*

## **SUFFIXES**

\_\_\_\_ -AL Adapter Lug

\_ -D Back to Back System

-E2 Concealed Arm Escutcheons 2 [51] Long

-WL Waste Line Sleeve

Zurn Industries, LLC | Specification Drainage Operation
1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929
In Canada | Zurn Industries Limited
3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292

Rev. F

Date: 09/27/2017 C.N. No. 137985

Prod. | Dwg. No. Z1231-EZR

installation.

<sup>\*</sup> Regularly furnished unless otherwise specified