



ARCHITECTURAL & ENGINEERING SPECIFICATION

Exposed, quiet diaphragm-type, chrome-plated flushometer valve with a polished exterior. Complete with chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve incorporates a 6VDC motor actuator, a battery powered automatic sensor, chrome-plated metal cover with manual override push button and 10 degree angled sensor.

PRODUCT FEATURES

- Control stop has internal siphon-guard protection, sweat solder kit, wall flange with set screw
- High back pressure vacuum breaker with one piece hex coupling nut
- Chloramine resistant internal seals
- Clog resistant, triple filtered by-pass
- Adjustable tailpiece
- Spud coupling and flange for top spud connection
- True mechanical override button

COMPLIANCE AND CERTIFICATION:

- Complies with ASSE 1037 / ASME A112.1037 / CSA B125.37
- ADA Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.

ZER6000AV-SM ZURN ONE SYSTEMS

Complete fixture package with bowl, flush valve, seat and trim

ITEM NUMBER	DESCRIPTION	FLUSH VOLUME GPF
Z.WC1.S	Z5615 Wall Hung System	1.1
Z.WC2.S	Z5615 Wall Hung System	1.28
Z.WC3.S	Z5655 Elongated standard height bowl system	1.1
Z.WC4.S	Z5655 Elongated standard height bowl system	1.28
Z.WC5.S	Z5654 Elongated 14" TAS height bowl system	1.28
Z.WC3.AS	Z5665 ADA height bowl system	1.1
Z.WC4.AS	Z5665 ADA height bowl system	1.28



FLOW OPTIONS

	FLUSH VOLUME GPF	WATERSENSE COMPLIANT
-ONE	1.1	☑
-HET	1.28	☑
-WS1	1.6	
-STANDARD	3.5	

SUFFIX OPTIONS

- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

VALVE HEIGHT OPTIONS

	DIMENSION A INCH [MM]	DIMENSION B INCH [MM]
-STANDARD	11 1/2" [292]	9 7/8" [251]
-1	16" [406]	14 3/8" [365]
-2	24" [610]	22 3/8" [568]
-3	27" [686]	25 3/8" [645]

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in/Overview dimensions:

