

TAG			
IAG			

### ARCHITECTURAL/ENGINEERING SPECIFICATION

The ZER EZ Gear-Driven Water Closet Retrofit Kit is performance engineered with the dual action of the ceramic disc cartridge and motor gear-driven operation. Its polished chrome-plated finish, modern top-mount design, and quiet diaphragm operation are ideal for new and retrofit commercial restroom applications.

#### **PRODUCT FEATURES**

- Zurn's TPE diaphragm Clog-resistant bypass Chloramine resistant
- Actuator

Electronic automatic sensor Gear-driven ceramic cartridge

- True Mechanical Override Button
- Chloramine-resistant internal seals
- Universal mounting kit supplied with threaded ring for Zurn and alternative manufacturers diaphragm valves
- · Operating Pressure

25 psi (running) - 80 psi (static) Higher running pressure may be required for some fixtures. Consult fixture manufacturer for details.

#### **COMPLIANCE AND CERTIFICATION**

ADA Compliant



## **FLOW OPTIONS**

	FLUSH VOLUME GPF	DUAL FLUSH GPF
-ONE	1.1	
-HET	1.28	
-WS1	1.6	1.6/1.1

## SUFFIX OPTIONS

-DF Dual Flush (See Chart Above)

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rev. A | Date: 6/05/2024 | C.N. No. 146084 | Prod./Dwg. No. SS ZERK-C-\_\_-TM-MOB



# Rough-in dimensions/Overview dimensions



