

TAG			
IAG			

ARCHITECTURAL/ENGINEERING SPECIFICATION

The ZER EZ Gear-Driven Urinal Retrofit Kit is performance engineered with the dual action of the ceramic disc cartridge and motor gear-driven operation. Its polished chrome-plated finish, modern top-mount design, and quiet diaphragm operation are ideal for new and retrofit commercial restroom applications.

PRODUCT FEATURES

- Zurn's TPE diaphragm Clog-resistant bypass Chloramine resistant
- Actuator

Electronic automatic sensor Gear-driven ceramic cartridge

- True Mechanical Override Button
- Chloramine-resistant internal seals
- Universal mounting kit supplied with threaded ring for Zurn and alternative manufacturers diaphragm valves
- Operating Pressure
 25 psi (running) 80 psi (static)
 Higher running pressure may be required for some fixtures. Consult



fixture manufacturer for details.

ADA Compliant



FLOW OPTIONS

. 2011 01 110110				
	FLUSH VOLUME GPF			
-ULF	0.125			
-EWS	0.5			
-WS1	1.0			

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rev. A | Date: 6/26/2024 | C.N. No. 146084 | Prod./Dwg. No. SS ZERK-U-__-TM-MOB



TAG _____

Rough-in dimensions/Overview dimensions



