



ZTR6203

Exposed Sensor Flush Valve for Urinals

TAG _____

Architectural/Engineering Specification:

Exposed, quiet piston-type, chrome plated flushometer valve with a polished exterior. Complete with chloramine resistant, filtered piston kit. The valve incorporates a 6VDC solenoid actuator, a battery powered automatic sensor with manual override push button, and robust vandal resistant metal cover with 10 degree angled sensor.

Product Features:

- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection and vandal resistant stop cap, Sweat solder kit, wall flange with set screw.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

Compliance and Certification:

- ADA Compliant



*This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.

Valve Height Options:

	Product No.	A	B
	ZTR6203 (Standard)	11 1/2" [292]	10 1/8 [257]
	ZTR6203-1	16" [406]	14 5/8 [378]



Flow Options:

	Flush Volume	WaterSense* Labeled
-ULF	0.125 gpf	✓
-QRT	0.25 gpf	✓
-EWS	0.5 gpf	✓
-WS1	1.0 gpf	

Suffix Options:

- LL 10 Year Long Life Battery
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in dimensions/Overview dimensions

