

TAG \_\_\_\_

### ARCHITECTURAL & ENGINEERING SPECIFICATION

Vitreous china, high efficiency, 1.28 gpf low consumption, high performance siphon-jet toilet with 3" flush valve, elongated front rim and 12" standard rough-in.

#### **PRODUCT FEATURES**

- 1.28 gpf (gallons per flush)
- High efficiency toilets (HET) reduces potable water usage over 20%
- Vitreous china
- 3" Flush valve for powerful flushing
- Chrome plated metal handle
- · Elongated front rim
- EcoVantage® siphon-jet design
- Extra large foot print for easy retro-fit
- 21/8" Fully glazed trapway
- Chloramine resistant internal components
- Maximum performance (MaP) score of 1000g
- Concealed sanitary bar
- 2 1/2" Trap seal
- 10" x 8" water surface
- Includes bolt caps
- Shipping weight: 89 lbs.

#### COMPLIANCE AND CERTIFICATION

- ADA Compliant
- WaterSense Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.

In Canada - Consult local codes and standards.



### OPTION

-RH	Vitreous China right-hand lever tank.

#### RECOMMENDED TRIM

Z5958SS-EL	Elongated, white, closed front toilet seat with cover & stainless steel check hinge.
Z5972-COMB	Closet bolt/wax ring kit.
Z8800-CR	Standard stop with flexible closet riser.

## OPTIONAL TRIM

Z5975-FLO-JR PVC Flo-Bowl Jr. closet flange kit

See Zurn One Systems for suggested packages.

Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

by **ZUIN ELKAY** Water Solutions



TAG \_\_\_\_\_

# Rough-in/Overview dimensions

