



ARCHITECTURAL & ENGINEERING SPECIFICATION

Exposed, quiet piston type, chrome plated flushometer valve with a polished exterior. Complete with Zurn's MetroVantage chloramine resistant filtered by-pass. The valve is ADA compliant with a non-hold open and no leak handle feature. Internal seals are made of chloramine resistant materials.

PRODUCT FEATURES

- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection, Sweat solder kit, wall flange with set screw.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

VALVE HEIGHT OPTIONS

	DIMENSION A INCH [MM]
-STANDARD	11 1/2" [292]
-1	16" [406]
-2	24" [610]
-3	27" [686]

COMPLIANCE AND CERTIFICATION

- ADA Compliant



*This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



FLOW OPTIONS

	FLUSH VOLUME GPF	DUAL FLUSH GPF	WATERSENSE* COMPLIANT
-HET	1.28		☑
-WS1	1.6	1.6/1.1	

SUFFIX OPTIONS

- BG BioCare ADAHandle
- DF Dual Flush (See Chart Above)
- L 1" [25mm] Metal Push Button
- VC Vandal Resistant Stop Cap
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in/Overview dimensions

