



# ZER6003AV-CPM

Sensor Operated Battery Powered Flush Valve for Urinals

TAG \_\_\_\_\_

### Architectural/Engineering Specification:

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with chloramine resistant, dual seal Zurn's AquaVantage® TPE diaphragm with a clog resistant by-pass. The valve incorporates a 6VDC motor actuator, an integral infrared convergence-type proximity sensor and a manual sensor with capacitive sensing push button override, high impact resistant polycarbonate housing and chrome plated plastic cover with manual override push button and 10 degree angled sensor.

### Product Features:

- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection and vandal resistant stop cap, Sweat solder kit, wall flange with set screw.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

### Compliance and Certification:

- ADA Compliant
- Complies with ASSE 1037/ASME A112.1037/CSA B125.37



\*This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.



### Flow Options:

	Flush Volume	WaterSense* Labeled
-ULF	0.125 gpf	✓
-EWS	0.5 gpf	✓
-WS1	1.0 gpf	

### Suffix Options:

- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support
- Other

Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



# ZER6003AV-CPM

Sensor Operated Battery Powered Flush Valve for Urinals

TAG \_\_\_\_\_

## Rough-in/Overview dimensions

