



# Model FP51

## Concentric Reducers



### Dimensions & Weights (do not include pkg.)


SIZE in.	MODEL	DIMENSIONS (approximate)		
		A in.	Max. Pressure PSI	Weight lbs.
2 X 1	2X1-FP51	2.52	400	0.3
2 X 1 1/4	2X114-FP51	2.52	400	0.3
2 X 1 1/2	2X112-FP51	2.52	400	0.3
2 1/2 X 1 1/4	212X114-FP51	2.52	400	0.9
2 1/2 X 1 1/2	212X112-FP51	2.52	400	0.4
2 1/2 X 2	212X2-FP51	2.52	400	0.5
3 X 1 1/2	3X112-FP51	2.52	400	1.1
3 X 2	3X2-FP51	2.52	400	0.7
3 X 2 1/2	3X212-FP51	2.52	400	0.6
4 X 2	4X2-FP51	3.00	400	2.2
4 X 2 1/2	4X212-FP51	3.00	400	2.0
4 X 3	4X3-FP51	3.00	400	2.1
6 X 2	6X2-FP51	4.02	300	4.2
6 X 2 1/2	6X212-FP51	4.02	300	4.0
6 X 3	6X3-FP51	4.02	300	3.9
6 X 4	6X4-FP51	4.02	300	3.9
8 X 3	8X3-FP51	5.00	300	7.9
8 X 4	8X4-FP51	5.00	300	8.2
8 X 6	8X6-FP51	5.00	300	8.3
10 X 6	10X6-FP51	5.98	300	36.5
10 X 8	10X8-FP51	5.98	300	38.0

### Application

Zurn reducers connect pipes of different sizes.



**4X212-FP51**



### Material

Casting ASTM A536 65-45-12 Ductile Iron

### Standards Compliance

- UL<sup>®</sup> Listed
- C-UL<sup>®</sup> Listed
- FM<sup>®</sup> Approved

### Features

Maximum Pressure:  
 2X - 4X 400 PSI  
 6X - 10X 300 PSI

### Options:

- GALV - With Hot Dipped Galvanized Coating