



Model: Z5572

Dual Flush Pressure Assist, Elongated,
Two-Piece Toilet

TAG _____

Architectural/Engineering Specification:

Zurn Z5572 Vitreous China floor mounted, Two Piece toilet, High Efficiency Dual Flush 1.6 gpf / 6.0 Lpf or 1.1 gpf / 4.2 Lpf, Pressure Assisted tank, Elongated standard height rim and 12" Rough-in.

Zurn Z5572 utilizes Zurn EcoVantage® dual-flush technology, offers an innovative water saving solution ideal for commercial applications.

Product Features:

- 1.6 gpf or 1.1 gpf flow rate
- High Efficiency Toilet (HET) reduces potable water usage over 30%
- Vitreous china
- Pressure assisted tank
- High performance EcoFlush™ technology
- Easy touch handle actuation
- Ultra quiet flush
- Siphon jet flush action
- 2-1/8" fully glazed trapway
- Operating pressure range 20-80 psi
- Elongated front rim
- Chrome plated handle
- Large water surface area
- Includes bolt caps
- Shipping weight: 95 lbs

Note: HET 1.1 gpf pressure assist tank also available. See models Z5571.

Compliance and Certification:

- ASME A112.19.2 / CSA B45.1

The Z5562-TNK-PA is WaterSense listed when paired with a Z5570-BWL.



Suffix Option:

- RH Vitreous China right-hand lever tank
- VL Vitreous China lid with vandal-proof lock down.

Recommended Trim:

-Z5972-COMB

Closet bolt & wax ring kit.

-Z5958SS-EL

Elongated, white, closed front toilet seat with cover & stainless steel check hinge.

-Z8800-CR

Standard stop with flexible closet riser.

Optional Trim

-Z5975-FLO-JR

PVC Flo-Bowl Jr. closet flange kit

See Zurn One Systems for suggested packages.

Architectural/Engineering Approval

Fixture dimensions meet ASME A112.19.2 / CSA B45.1 requirements.

In Canada - Consult local codes and standards.

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

